

[Original document](#)

SUBSCRIBER LINE TERMINATOR

Patent number: JP10322460
Publication date: 1998-12-04
Inventor: MACHIDA SHINICHI
Applicant: MATSUSHITA ELECTRIC IND CO LTD
Classification:
- international: ***H04B10/04; H04B10/06; H04B10/12; H04B10/13; H04B10/135; H04B10/14; H04B10/24; H04B10/26; H04B10/28; H04L29/00; H04M11/00; H04M19/08; H04B10/04; H04B10/06; H04B10/12; H04B10/13; H04B10/135; H04B10/14; H04B10/24; H04B10/26; H04B10/28; H04L29/00; H04M11/00; H04M19/08;*** (IPC1-7): H04M11/00; H04B10/04; H04B10/06; H04B10/12; H04B10/13; H04B10/135; H04B10/14; H04B10/24; H04B10/26; H04B10/28; H04L29/00; H04M19/08
- european:
Application number: JP19970129503 19970520
Priority number(s): JP19970129503 19970520


[View INPADOC patent family](#)

[Report a data error here](#)

Abstract of **JP10322460**

PROBLEM TO BE SOLVED: To make a subscriber line terminator small-sized and to reduce the cost with respect to the subscriber line terminator that conducts transmission reception between a subscriber and a station by using multiplexed signals on a transmission line. **SOLUTION:** A subscriber line terminator (N-ONU) 10 makes communication processing of an optical signal whose wavelength is 1.3 μm from a station and an AC/DC conversion circuit 21 and a DC/DC conversion circuit 22 supply power to a signal processing circuit 31. The other subscriber line terminator (V-ONU) 110 makes communication processing of an optical signal whose wavelength is 1.5 μm from a station and the AC/DC conversion circuit 21 supplies power to a DC/DC conversion circuit 122 which supplies power to a signal processing circuit 131. Then the AC/DC conversion circuit

21 supplies power so as to make the power supply means in common for the operation of the N-ONU 10 and the V-ONU 11, thereby making the size of the terminator small.



Data supplied from the *esp@cenet* database - Worldwide